

856 Ship Notice/Manifest

Functional Group ID=**SH**

Introduction:

This Draft Standard for Trial Use contains the format and establishes the data contents of the Ship Notice/Manifest Transaction Set (856) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to list the contents of a shipment of goods as well as additional information relating to the shipment, such as order information, product description, physical characteristics, type of packaging, marking, carrier information, and configuration of goods within the transportation equipment. The transaction set enables the sender to describe the contents and configuration of a shipment in various levels of detail and provides an ordered flexibility to convey information. The sender of this transaction is the organization responsible for detailing and communicating the contents of a shipment, or shipments, to one or more receivers of the transaction set. The receiver of this transaction set can be any organization having an interest in the contents of a shipment or information about the contents of a shipment.

Heading:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
M	0100	ST	Transaction Set Header	M	1		
M	0200	BSN	Beginning Segment for Ship Notice	M	1		
M	0400	DTM	Date/Time Reference	M	10		

Detail:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
						200000	
LOOP ID - HL							
M	0100	HL	Hierarchical Level	M	1		c1
M	0200	LIN	Item Identification	M	1		
M	0300	SN1	Item Detail (Shipment)	M	1		
M	0500	PRF	Purchase Order Reference	M	1		
M	1100	TD1	Carrier Details (Quantity and Weight)	M	20		
M	1200	TD5	Carrier Details (Routing Sequence/Transit Time)	M	12		
M	1700	REF	Reference Identification	M	1		
	1700	REF	Reference Identification	O	1		
	1700	REF	Reference Identification	O	1		
	1700	REF	Reference Identification	O	1		
						200	
LOOP ID - N1							
M	2200	N1	Name	M	1		
	2300	N2	Additional Name Information	O	2		
M	2400	N3	Address Information	M	2		
M	2500	N4	Geographic Location	M	1		
						200	
LOOP ID - N1							
M	2200	N1	Name	M	1		
	2300	N2	Additional Name Information	O	2		
M	2400	N3	Address Information	M	2		
M	2500	N4	Geographic Location	M	1		
						200000	
LOOP ID - HL							
M	0100	HL	Hierarchical Level	M	1		

M	0200	LIN	Item Identification	M	1
M	0300	SN1	Item Detail (Shipment)	M	1
	1700	REF	Reference Identification	O	1
LOOP ID - HL					200000
M	0100	HL	Hierarchical Level	M	1
M	0200	LIN	Item Identification	M	1
M	0300	SN1	Item Detail (Shipment)	M	1
	1700	REF	Reference Identification	O	1
LOOP ID - HL					200000
M	0100	HL	Hierarchical Level	M	1
M	0200	LIN	Item Identification	M	1
M	0300	SN1	Item Detail (Shipment)	M	1
	1700	REF	Reference Identification	O	1

Summary:

	<u>Pos. No.</u>	<u>Seg. ID</u>	<u>Name</u>	<u>Req. Des.</u>	<u>Max.Use</u>	<u>Loop Repeat</u>	<u>Notes and Comments</u>
M	0200	SE	Transaction Set Trailer	M	1		

Transaction Set Comments

1. The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.

Segment: **ST** Transaction Set Header
Position: 0100
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To indicate the start of a transaction set and to assign a control number
Syntax Notes:
Semantic Notes:

- 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
- 2 The implementation convention reference (ST03) is used by the translation routines of the interchange partners to select the appropriate implementation convention to match the transaction set definition.

Comments:

Business Rules: Variable Name: STST

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	ST01	143	Transaction Set Identifier Code Code uniquely identifying a Transaction Set 856	M 1 ID 3/3
M	ST02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set System Generated	M 1 AN 4/9
X	ST03	1705	Implementation Convention Reference	O 1 AN 1/35

Segment: **BSN** Beginning Segment for Ship Notice
Position: 0200
Loop:
Level: Heading
Usage: Mandatory
Max Use: 1
Purpose: To transmit identifying numbers, dates, and other basic data relating to the transaction set
Syntax Notes: 1 If BSN07 is present, then BSN06 is required.
Semantic Notes: 1 BSN03 is the date the shipment transaction set is created.
 2 BSN04 is the time the shipment transaction set is created.
 3 BSN06 is limited to shipment related codes.
Comments: 1 BSN06 and BSN07 differentiate the functionality of use for the transaction set.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	BSN01	353	Transaction Set Purpose Code Code identifying purpose of transaction set 00=Original 01=Cancellation 02=Add 03=Delete 04=Change 05=Replace CO=Corrected Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/2
M	BSN02	396	Shipment Identification A unique control number assigned by the original shipper to identify a specific shipment	M 1 AN 2/30
M	BSN03	373	Date Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year YYYYMMDD	M 1 DT 8/8
M	BSN04	337	Time Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99) HHMM	M 1 TM 4/8
	BSN05	1005	Hierarchical Structure Code Code indicating the hierarchical application structure of a transaction set that utilizes the HL segment to define the structure of the transaction set Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 4/4
	BSN06	640	Transaction Type Code Code specifying the type of transaction Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
	BSN07	641	Status Reason Code Code indicating the status reason Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 3/3

Segment: **DTM** Date/Time Reference
Position: 0400
Loop:
Level: Heading
Usage: Mandatory
Max Use: 10
Purpose: To specify pertinent dates and times
Syntax Notes:

- 1 At least one of DTM02 DTM03 or DTM05 is required.
- 2 If DTM04 is present, then DTM03 is required.
- 3 If either DTM05 or DTM06 is present, then the other is required.

Semantic Notes:
Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	DTM01	374	Date/Time Qualifier Code specifying type of date or time, or both date and time 011=SHIPPED Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 3/3
M	DTM02	373	Date Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year YYYYMMDD Date the item was shipped	M 1 DT 8/8
	DTM03	337	Time Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99) HHMM Time the item was shipped	X 1 TM 4/8
	DTM04	623	Time Code Code identifying the time. In accordance with International Standards Organization standard 8601, time can be specified by a + or - and an indication in hours in relation to Universal Time Coordinate (UTC) time; since + is a restricted character, + and - are substituted by P and M in the codes that follow ET=Eastern Time CT=Central Time MT=Mountain Time PT=Pacific Time Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 2/2
X	DTM05	1250	Date Time Period Format Qualifier Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/3
X	DTM06	1251	Date Time Period	X 1 AN 1/35

Segment: **HL** Hierarchical Level
Position: 0100
Loop: HL Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Syntax Notes:
Semantic Notes:

- Comments:**
- 1 The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
The HL segment defines a top-down/left-right ordered structure.
 - 2 HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
 - 3 HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
 - 4 HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
 - 5 HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

Data Element Summary

Ref.	Data Element	Name	Attributes
M	HL01	628 Hierarchical ID Number A unique number assigned by the sender to identify a particular data segment in a hierarchical structure 1	M 1 AN 1/12
	HL02	734 Hierarchical Parent ID Number Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to BLANK	O 1 AN 1/12
M	HL03	735 Hierarchical Level Code Code defining the characteristic of a level in a hierarchical structure S = Shipment I = Item O = Order P = Pack Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 1/2
X	HL04	736 Hierarchical Child Code Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 1/1

Segment:	LIN Item Identification
Position:	0200
Loop:	HL Mandatory
Level:	Detail
Usage:	Mandatory
Max Use:	1
Purpose:	To specify basic item identification data
Syntax Notes:	<ol style="list-style-type: none"> 1 If either LIN04 or LIN05 is present, then the other is required. 2 If either LIN06 or LIN07 is present, then the other is required. 3 If either LIN08 or LIN09 is present, then the other is required. 4 If either LIN10 or LIN11 is present, then the other is required. 5 If either LIN12 or LIN13 is present, then the other is required. 6 If either LIN14 or LIN15 is present, then the other is required. 7 If either LIN16 or LIN17 is present, then the other is required. 8 If either LIN18 or LIN19 is present, then the other is required. 9 If either LIN20 or LIN21 is present, then the other is required. 10 If either LIN22 or LIN23 is present, then the other is required. 11 If either LIN24 or LIN25 is present, then the other is required. 12 If either LIN26 or LIN27 is present, then the other is required. 13 If either LIN28 or LIN29 is present, then the other is required. 14 If either LIN30 or LIN31 is present, then the other is required.
Semantic Notes:	1 LIN01 is the line item identification
Comments:	<ol style="list-style-type: none"> 1 See the Data Dictionary for a complete list of IDs. 2 LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Data Element Summary

Ref.	Data	Name	Attributes
Des.	Element	Name	Attributes
M	LIN01	350 Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	M 1 AN 1/20
M	LIN02	235 Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) "VP" which stands for Vendor's (Seller) Part Number Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/2
M	LIN03	234 Product/Service ID Identifying number for a product or service Product Number	M 1 AN 1/48
M	LIN04	235 Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) BP=Buyer's Part Number or PI= Purchaser's Item Number Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/2
M	LIN05	234 Product/Service ID Identifying number for a product or service Buyer's Part Number	M 1 AN 1/48
X	LIN06	235 Product/Service ID Qualifier Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
X	LIN07	234 Product/Service ID	X 1 AN 1/48
X	LIN08	235 Product/Service ID Qualifier Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
X	LIN09	234 Product/Service ID	X 1 AN 1/48
X	LIN10	235 Product/Service ID Qualifier Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
X	LIN11	234 Product/Service ID	X 1 AN 1/48
X	LIN12	235 Product/Service ID Qualifier	X 1 ID 2/2

			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN13	234	Product/Service ID	X	1 AN 1/48
X	LIN14	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN15	234	Product/Service ID	X	1 AN 1/48
X	LIN16	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN17	234	Product/Service ID	X	1 AN 1/48
X	LIN18	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN19	234	Product/Service ID	X	1 AN 1/48
X	LIN20	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN21	234	Product/Service ID	X	1 AN 1/48
X	LIN22	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN23	234	Product/Service ID	X	1 AN 1/48
X	LIN24	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN25	234	Product/Service ID	X	1 AN 1/48
X	LIN26	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN27	234	Product/Service ID	X	1 AN 1/48
X	LIN28	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN29	234	Product/Service ID	X	1 AN 1/48
X	LIN30	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN31	234	Product/Service ID	X	1 AN 1/48

Segment: **SN1** Item Detail (Shipment)
Position: 0300
Loop: HL Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To specify line-item detail relative to shipment
Syntax Notes: 1 If either SN105 or SN106 is present, then the other is required.
Semantic Notes: 1 SN101 is the ship notice line-item identification.
Comments: 1 SN103 defines the unit of measurement for both SN102 and SN104.

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
	<u>Des.</u>	<u>Element</u>		
M	SN101	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	M 1 AN 1/20
M	SN102	382	Number of Units Shipped Numeric value of units shipped in manufacturer's shipping units for a line item or transaction set	M 1 R 1/10
M	SN103	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken EA= Each Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/2
	SN104	646	Quantity Shipped to Date Number of units shipped to date	O 1 R 1/15
	SN105	330	Quantity Ordered Quantity ordered	X 1 R 1/15
	SN106	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
	SN107	728	Returnable Container Load Make-Up Code Code identifying the load make-up of the returnable containers in the shipment Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 1/2
	SN108	668	Line Item Status Code Code specifying the action taken by the seller on a line item requested by the buyer Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 2/2

Segment: **PRF** Purchase Order Reference
Position: 0500
Loop: HL Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To provide reference to a specific purchase order
Syntax Notes:
Semantic Notes: 1 PRF04 is the date assigned by the purchaser to purchase order.
Comments:

Data Element Summary

	<u>Ref.</u>	<u>Data</u>	<u>Name</u>	<u>Attributes</u>
M	<u>Des.</u>	<u>Element</u>		
	PRF01	324	Purchase Order Number Identifying number for Purchase Order assigned by the orderer/purchaser	M 1 AN 1/22
	PRF02	328	Release Number Number identifying a release against a Purchase Order previously placed by the parties involved in the transaction	O 1 AN 1/30
	PRF03	327	Change Order Sequence Number Number assigned by the orderer identifying a specific change or revision to a previously transmitted transaction set	O 1 AN 1/8
	PRF04	373	Date Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year	O 1 DT 8/8
	PRF05	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	O 1 AN 1/20
	PRF06	367	Contract Number Contract number	O 1 AN 1/30
	PRF07	92	Purchase Order Type Code Code specifying the type of Purchase Order Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 2/2

Segment: **TD1** Carrier Details (Quantity and Weight)
Position: 1100
Loop: HL Mandatory
Level: Detail
Usage: Mandatory
Max Use: 20
Purpose: To specify the transportation details relative to commodity, weight, and quantity
Syntax Notes:

- 1 If TD101 is present, then TD102 is required.
- 2 If TD103 is present, then TD104 is required.
- 3 If TD106 is present, then TD107 is required.
- 4 If either TD107 or TD108 is present, then the other is required.
- 5 If either TD109 or TD110 is present, then the other is required.

Semantic Notes:
Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	TD101	103	Packaging Code Code identifying the type of packaging; Part 1: Packaging Form, Part 2: Packaging Material; if the Data Element is used, then Part 1 is always required BAG= Bag BBL= Barrel BOX= Box CAS= Case CNT= Container DRM= Drum PCS= Pieces PCK= Package PLT= Pallet ROL= Roll SHT= Sheet SPL= Spool TNK= Tank Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 AN 3/5
M	TD102	80	Lading Quantity Number of units (pieces) of the lading commodity	M 1 N0 1/7
	TD103	23	Commodity Code Qualifier Code identifying the commodity coding system used for Commodity Code Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 1/1
	TD104	22	Commodity Code Code describing a commodity or group of commodities	X 1 AN 1/30
	TD105	79	Lading Description Description of an item as required for rating and billing purposes	O 1 AN 1/50
	TD106	187	Weight Qualifier Code defining the type of weight G= Gross Weight N= Actual Net Weight Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 1/2
	TD107	81	Weight Numeric value of weight	X 1 R 1/10
	TD108	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken	X 1 ID 2/2

LB= Pounds
OZ= Ounce- Av
TG= Gross Ton

Refer to 004030 Data Element Dictionary for acceptable code values.

TD109 **183** **Volume** **X** **1 R 1/8**
Value of volumetric measure

TD110 **355** **Unit or Basis for Measurement Code** **X** **1 ID 2/2**
Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken
Refer to 004030 Data Element Dictionary for acceptable code values.

Segment: **TD5** Carrier Details (Routing Sequence/Transit Time)

Position: 1200

Loop: HL Mandatory

Level: Detail

Usage: Mandatory

Max Use: 12

Purpose: To specify the carrier and sequence of routing and provide transit time information

Syntax Notes:

- 1 At least one of TD502 TD504 TD505 TD506 or TD512 is required.
- 2 If TD502 is present, then TD503 is required.
- 3 If TD507 is present, then TD508 is required.
- 4 If TD510 is present, then TD511 is required.
- 5 If TD513 is present, then TD512 is required.
- 6 If TD514 is present, then TD513 is required.
- 7 If TD515 is present, then TD512 is required.

Semantic Notes:

- 1 TD515 is the country where the service is to be performed.

Comments:

- 1 When specifying a routing sequence to be used for the shipment movement in lieu of specifying each carrier within the movement, use TD502 to identify the party responsible for defining the routing sequence, and use TD503 to identify the actual routing sequence, specified by the party identified in TD502.

Data Element Summary

Ref.	Data	Name	Attributes
<u>Des.</u>	<u>Element</u>		
M	TD501	133 Routing Sequence Code Code describing the relationship of a carrier to a specific shipment movement B Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 1/2
M	TD502	66 Identification Code Qualifier Code designating the system/method of code structure used for Identification Code (67) 2 Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 1/2
M	TD503	67 Identification Code Code identifying a party or other code CARRIER'S SCAC CODE	M 1 AN 2/80
M	TD504	91 Transportation Method/Type Code Code specifying the method or type of transportation for the shipment A=Air D=Parcel Post E=Expedited Truck M=Motor (common carrier) LT=Less than truck load X=Intermodal (Piggyback) ZZ=Mutually Defined Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 1/2
	TD505	387 Routing Free-form description of the routing or requested routing for shipment, or the originating carrier's identity Description of the service level of the shipment. Examples (UPS-GROUND, UPS-2ND DAY, UPS-NEXT DAY, MOTOR CARRIER, etc)	O 1 AN 1/35
	TD506	368 Shipment/Order Status Code Code indicating the status of an order or shipment or the disposition of any difference between the quantity ordered and the quantity shipped for a line item or transaction Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2

TD507	309	Location Qualifier Code identifying type of location Refer to 004030 Data Element Dictionary for acceptable code values.	O	1	ID 1/2
TD508	310	Location Identifier Code which identifies a specific location	X	1	AN 1/30
TD509	731	Transit Direction Code The point of origin and point of direction Refer to 004030 Data Element Dictionary for acceptable code values.	O	1	ID 2/2
TD510	732	Transit Time Direction Qualifier Code specifying the value of time used to measure the transit time Refer to 004030 Data Element Dictionary for acceptable code values.	O	1	ID 2/2
TD511	733	Transit Time The numeric amount of transit time	X	1	R 1/4
TD512	284	Service Level Code Code indicating the level of transportation service or the billing service offered by the transportation carrier D1= Next Day D2= Second Day D3=Third Day SG=Standard Ground Refer to 004030 Data Element Dictionary for acceptable code values.	O	1	ID 2/2
TD513	284	Service Level Code Code indicating the level of transportation service or the billing service offered by the transportation carrier Refer to 004030 Data Element Dictionary for acceptable code values.	X	1	ID 2/2
TD514	284	Service Level Code Code indicating the level of transportation service or the billing service offered by the transportation carrier Refer to 004030 Data Element Dictionary for acceptable code values.	O	1	ID 2/2
TD515	26	Country Code Code identifying the country	O	1	ID 2/3

Segment: **REF** Reference Identification
Position: 1700
Loop: HL Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>	
M	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification	M	1 ID 2/3
			CN Refer to 004030 Data Element Dictionary for acceptable code values.		
M	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M	1 AN 1/50
			Shipment Tracking Number		
	REF03	352	Description A free-form description to clarify the related data elements and their content	X	1 AN 1/80
X	REF04	C040	Reference Identifier To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier	O	1
X	C04001	128	Reference Identification Qualifier Code qualifying the Reference Identification	M	ID 2/3
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	C04002	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M	AN 1/50
X	C04003	128	Reference Identification Qualifier Code qualifying the Reference Identification	X	ID 2/3
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	C04004	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN 1/50
X	C04005	128	Reference Identification Qualifier Code qualifying the Reference Identification	X	ID 2/3
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	C04006	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN 1/50

Segment: **REF** Reference Identification
Position: 1700
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>	
M	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification LS= Container ID: on the container label Refer to 004030 Data Element Dictionary for acceptable code values.	M	1 ID 2/3
M	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier UCC 128	M	1 AN 1/50
	REF03	352	Description A free-form description to clarify the related data elements and their content	X	1 AN 1/80
X	REF04	C040	Reference Identifier To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier	O	1
X	C04001	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	M	ID 2/3
X	C04002	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M	AN 1/50
X	C04003	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	X	ID 2/3
X	C04004	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN 1/50
X	C04005	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	X	ID 2/3
X	C04006	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN 1/50

Segment: **REF** Reference Identification
Position: 1700
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>	
M	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification PK=Packing List Number Refer to 004030 Data Element Dictionary for acceptable code values.	M	1 ID 2/3
M	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier Packing List Number	M	1 AN 1/50
	REF03	352	Description A free-form description to clarify the related data elements and their content	X	1 AN 1/80
X	REF04	C040	Reference Identifier To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier	O	1
X	C04001	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	M	ID 2/3
X	C04002	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M	AN 1/50
X	C04003	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	X	ID 2/3
X	C04004	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN 1/50
X	C04005	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	X	ID 2/3
X	C04006	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN 1/50

Segment: **REF** Reference Identification
Position: 1700
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification BM= BOL # Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/3
M	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier BOL #	M 1 AN 1/50
	REF03	352	Description A free-form description to clarify the related data elements and their content	X 1 AN 1/80
X	REF04	C040	Reference Identifier To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier	O 1
X	C04001	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	M ID 2/3
X	C04002	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M AN 1/50
X	C04003	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	X ID 2/3
X	C04004	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X AN 1/50
X	C04005	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	X ID 2/3
X	C04006	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X AN 1/50

Segment: **N1** Name
Position: 2200
Loop: N1 Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To identify a party by type of organization, name, and code
Syntax Notes: 1 At least one of N102 or N103 is required.
 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:
Comments: 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
 2 N105 and N106 further define the type of entity in N101.

Data Element Summary

	Ref. Des.	Data Element	Name	Attributes
M	N101	98	Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual SF=Ship From Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/3
M	N102	93	Name Free-form name	M 1 AN 1/60
	N103	66	Identification Code Qualifier Code designating the system/method of code structure used for Identification Code (67) Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 1/2
	N104	67	Identification Code Code identifying a party or other code	X 1 AN 2/80
X	N105	706	Entity Relationship Code Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 2/2
X	N106	98	Entity Identifier Code Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 2/3

Segment: N2 Additional Name Information
Position: 2300
Loop: N1 Mandatory
Level: Detail
Usage: Optional
Max Use: 2
Purpose: To specify additional names
Syntax Notes:
Semantic Notes:
Comments:

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	N201	93	Name Free-form name Use for additional Sender's name information.	M 1 AN 1/60
	N202	93	Name Free-form name Use for additional Sender's name information.	O 1 AN 1/60

Segment: N3 Address Information
Position: 2400
Loop: N1 Mandatory
Level: Detail
Usage: Mandatory
Max Use: 2
Purpose: To specify the location of the named party
Syntax Notes:
Semantic Notes:
Comments:

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	N301	166	Address Information Address information	M 1 AN 1/55
	N302	166	Address Information Address information	O 1 AN 1/55

Segment: **N4 Geographic Location**
Position: 2500
Loop: N1 Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To specify the geographic place of the named party
Syntax Notes:

- 1 Only one of N402 or N407 may be present.
- 2 If N406 is present, then N405 is required.
- 3 If N407 is present, then N404 is required.

Semantic Notes:
Comments:

- 1 A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
- 2 N402 is required only if city name (N401) is in the U.S. or Canada.

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	N401	19	City Name Free-form text for city name	M 1 AN 2/30
M	N402	156	State or Province Code Code (Standard State/Province) as defined by appropriate government agency Two letter state abbreviation.	M 1 ID 2/2
M	N403	116	Postal Code Code defining international postal zone code excluding punctuation and blanks (zip code for United States) 3 to 15 alphanumeric zip code	M 1 ID 3/15
M	N404	26	Country Code Code identifying the country 2 or 3 country code	M 1 ID 2/3
	N405	309	Location Qualifier Code identifying type of location Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 1/2
	N406	310	Location Identifier Code which identifies a specific location	O 1 AN 1/30
	N407	1715	Country Subdivision Code Code identifying the country subdivision	X 1 ID 1/3

Segment: **N1** Name
Position: 2200
Loop: N1 Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To identify a party by type of organization, name, and code
Syntax Notes: 1 At least one of N102 or N103 is required.
 2 If either N103 or N104 is present, then the other is required.
Semantic Notes:
Comments: 1 This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
 2 N105 and N106 further define the type of entity in N101.

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	N101	98	Entity Identifier Code Code identifying an organizational entity, a physical location, property or an individual ST=Ship To CN=Consignee UC=Ultimate Consignee Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/3
M	N102	93	Name Free-form name	M 1 AN 1/60
	N103	66	Identification Code Qualifier Code designating the system/method of code structure used for Identification Code (67) Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 1/2
	N104	67	Identification Code Code identifying a party or other code	X 1 AN 2/80
X	N105	706	Entity Relationship Code Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 2/2
X	N106	98	Entity Identifier Code Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 2/3

Segment: N2 Additional Name Information
Position: 2300
Loop: N1 Mandatory
Level: Detail
Usage: Optional
Max Use: 2
Purpose: To specify additional names
Syntax Notes:
Semantic Notes:
Comments:

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	N201	93	Name Free-form name Use for additional Sender's name information.	M 1 AN 1/60
	N202	93	Name Free-form name Use for additional Sender's name information.	O 1 AN 1/60

Segment: N3 Address Information
Position: 2400
Loop: N1 Mandatory
Level: Detail
Usage: Mandatory
Max Use: 2
Purpose: To specify the location of the named party
Syntax Notes:
Semantic Notes:
Comments:

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	N301	166	Address Information Address information	M 1 AN 1/55
	N302	166	Address Information Address information	O 1 AN 1/55

Segment: **N4 Geographic Location**
Position: 2500
Loop: N1 Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To specify the geographic place of the named party
Syntax Notes:

- 1 Only one of N402 or N407 may be present.
- 2 If N406 is present, then N405 is required.
- 3 If N407 is present, then N404 is required.

Semantic Notes:
Comments:

- 1 A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
- 2 N402 is required only if city name (N401) is in the U.S. or Canada.

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	N401	19	City Name Free-form text for city name	M 1 AN 2/30
M	N402	156	State or Province Code Code (Standard State/Province) as defined by appropriate government agency Two letter state abbreviation.	M 1 ID 2/2
M	N403	116	Postal Code Code defining international postal zone code excluding punctuation and blanks (zip code for United States) 3 to 15 alphanumeric zip code	M 1 ID 3/15
M	N404	26	Country Code Code identifying the country 2 or 3 country code	M 1 ID 2/3
	N405	309	Location Qualifier Code identifying type of location Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 1/2
	N406	310	Location Identifier Code which identifies a specific location	O 1 AN 1/30
	N407	1715	Country Subdivision Code Code identifying the country subdivision	X 1 ID 1/3

Segment: **HL** Hierarchical Level
Position: 0100
Loop: HL Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Syntax Notes:
Semantic Notes:

- Comments:**
- 1 The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
The HL segment defines a top-down/left-right ordered structure.
 - 2 HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
 - 3 HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
 - 4 HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
 - 5 HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

Data Element Summary

Ref.	Data Element	Name	Attributes
M	HL01	628 Hierarchical ID Number A unique number assigned by the sender to identify a particular data segment in a hierarchical structure	M 1 AN 1/12
	HL02	734 Hierarchical Parent ID Number Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to	O 1 AN 1/12
M	HL03	735 Hierarchical Level Code Code defining the characteristic of a level in a hierarchical structure S = Shipment I = Item O = Order P = Pack Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 1/2
	HL04	736 Hierarchical Child Code Code indicating if there are hierarchical child data segments subordinate to the level being described Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 1/1

Segment:	LIN Item Identification
Position:	0200
Loop:	HL Mandatory
Level:	Detail
Usage:	Mandatory
Max Use:	1
Purpose:	To specify basic item identification data
Syntax Notes:	<ol style="list-style-type: none"> 1 If either LIN04 or LIN05 is present, then the other is required. 2 If either LIN06 or LIN07 is present, then the other is required. 3 If either LIN08 or LIN09 is present, then the other is required. 4 If either LIN10 or LIN11 is present, then the other is required. 5 If either LIN12 or LIN13 is present, then the other is required. 6 If either LIN14 or LIN15 is present, then the other is required. 7 If either LIN16 or LIN17 is present, then the other is required. 8 If either LIN18 or LIN19 is present, then the other is required. 9 If either LIN20 or LIN21 is present, then the other is required. 10 If either LIN22 or LIN23 is present, then the other is required. 11 If either LIN24 or LIN25 is present, then the other is required. 12 If either LIN26 or LIN27 is present, then the other is required. 13 If either LIN28 or LIN29 is present, then the other is required. 14 If either LIN30 or LIN31 is present, then the other is required.
Semantic Notes:	1 LIN01 is the line item identification
Comments:	<ol style="list-style-type: none"> 1 See the Data Dictionary for a complete list of IDs. 2 LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Data Element Summary

Ref.	Data	Name	Attributes
Des.	Element	Name	Attributes
M	LIN01	350 Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	M 1 AN 1/20
M	LIN02	235 Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) "VP" which stands for Vendor's (Seller) Part Number Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/2
M	LIN03	234 Product/Service ID Identifying number for a product or service Product Number	M 1 AN 1/48
M	LIN04	235 Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) BP=Buyer's Part Number or PI= Purchaser's Item Number Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/2
M	LIN05	234 Product/Service ID Identifying number for a product or service Buyer's Part Number	M 1 AN 1/48
X	LIN06	235 Product/Service ID Qualifier Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
X	LIN07	234 Product/Service ID	X 1 AN 1/48
X	LIN08	235 Product/Service ID Qualifier Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
X	LIN09	234 Product/Service ID	X 1 AN 1/48
X	LIN10	235 Product/Service ID Qualifier Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
X	LIN11	234 Product/Service ID	X 1 AN 1/48
X	LIN12	235 Product/Service ID Qualifier	X 1 ID 2/2

			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN13	234	Product/Service ID	X	1 AN 1/48
X	LIN14	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN15	234	Product/Service ID	X	1 AN 1/48
X	LIN16	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN17	234	Product/Service ID	X	1 AN 1/48
X	LIN18	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN19	234	Product/Service ID	X	1 AN 1/48
X	LIN20	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN21	234	Product/Service ID	X	1 AN 1/48
X	LIN22	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN23	234	Product/Service ID	X	1 AN 1/48
X	LIN24	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN25	234	Product/Service ID	X	1 AN 1/48
X	LIN26	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN27	234	Product/Service ID	X	1 AN 1/48
X	LIN28	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN29	234	Product/Service ID	X	1 AN 1/48
X	LIN30	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN31	234	Product/Service ID	X	1 AN 1/48

Segment: **SN1** Item Detail (Shipment)
Position: 0300
Loop: HL Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To specify line-item detail relative to shipment
Syntax Notes: 1 If either SN105 or SN106 is present, then the other is required.
Semantic Notes: 1 SN101 is the ship notice line-item identification.
Comments: 1 SN103 defines the unit of measurement for both SN102 and SN104.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	SN101	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	M 1 AN 1/20
M	SN102	382	Number of Units Shipped Numeric value of units shipped in manufacturer's shipping units for a line item or transaction set	M 1 R 1/10
M	SN103	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken EA= Each Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/2
	SN104	646	Quantity Shipped to Date Number of units shipped to date	O 1 R 1/15
	SN105	330	Quantity Ordered Quantity ordered	X 1 R 1/15
	SN106	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
	SN107	728	Returnable Container Load Make-Up Code Code identifying the load make-up of the returnable containers in the shipment Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 1/2
	SN108	668	Line Item Status Code Code specifying the action taken by the seller on a line item requested by the buyer Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 2/2

Segment: **REF** Reference Identification
Position: 1700
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>	
M	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification LS= Container ID: on the container label Refer to 004030 Data Element Dictionary for acceptable code values.	M	1 ID 2/3
M	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier UCC 128	M	1 AN 1/50
	REF03	352	Description A free-form description to clarify the related data elements and their content	X	1 AN 1/80
X	REF04	C040	Reference Identifier To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier	O	1
X	C04001	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	M	ID 2/3
X	C04002	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M	AN 1/50
X	C04003	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	X	ID 2/3
X	C04004	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN 1/50
X	C04005	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	X	ID 2/3
X	C04006	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN 1/50

Segment: **HL** Hierarchical Level
Position: 0100
Loop: HL Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Syntax Notes:
Semantic Notes:

- Comments:**
- 1 The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
The HL segment defines a top-down/left-right ordered structure.
 - 2 HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
 - 3 HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
 - 4 HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
 - 5 HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

Data Element Summary

Ref.	Data Element	Name	Attributes
M	HL01	Hierarchical ID Number A unique number assigned by the sender to identify a particular data segment in a hierarchical structure	M 1 AN 1/12
		3	
	HL02	Hierarchical Parent ID Number Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to	O 1 AN 1/12
		1	
M	HL03	Hierarchical Level Code Code defining the characteristic of a level in a hierarchical structure	M 1 ID 1/2
		S = Shipment I = Item O = Order P = Pack	
		Refer to 004030 Data Element Dictionary for acceptable code values.	
	HL04	Hierarchical Child Code Code indicating if there are hierarchical child data segments subordinate to the level being described	O 1 ID 1/1
		Refer to 004030 Data Element Dictionary for acceptable code values.	

Segment:	LIN Item Identification
Position:	0200
Loop:	HL Mandatory
Level:	Detail
Usage:	Mandatory
Max Use:	1
Purpose:	To specify basic item identification data
Syntax Notes:	<ol style="list-style-type: none"> 1 If either LIN04 or LIN05 is present, then the other is required. 2 If either LIN06 or LIN07 is present, then the other is required. 3 If either LIN08 or LIN09 is present, then the other is required. 4 If either LIN10 or LIN11 is present, then the other is required. 5 If either LIN12 or LIN13 is present, then the other is required. 6 If either LIN14 or LIN15 is present, then the other is required. 7 If either LIN16 or LIN17 is present, then the other is required. 8 If either LIN18 or LIN19 is present, then the other is required. 9 If either LIN20 or LIN21 is present, then the other is required. 10 If either LIN22 or LIN23 is present, then the other is required. 11 If either LIN24 or LIN25 is present, then the other is required. 12 If either LIN26 or LIN27 is present, then the other is required. 13 If either LIN28 or LIN29 is present, then the other is required. 14 If either LIN30 or LIN31 is present, then the other is required.
Semantic Notes:	1 LIN01 is the line item identification
Comments:	<ol style="list-style-type: none"> 1 See the Data Dictionary for a complete list of IDs. 2 LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Data Element Summary

Ref.	Data	Name	Attributes
Des.	Element	Name	Attributes
M	LIN01	350 Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	M 1 AN 1/20
M	LIN02	235 Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) "VP" which stands for Vendor's (Seller) Part Number Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/2
M	LIN03	234 Product/Service ID Identifying number for a product or service Product Number	M 1 AN 1/48
M	LIN04	235 Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) BP=Buyer's Part Number or PI= Purchaser's Item Number Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/2
M	LIN05	234 Product/Service ID Identifying number for a product or service Buyer's Part Number	M 1 AN 1/48
X	LIN06	235 Product/Service ID Qualifier Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
X	LIN07	234 Product/Service ID	X 1 AN 1/48
X	LIN08	235 Product/Service ID Qualifier Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
X	LIN09	234 Product/Service ID	X 1 AN 1/48
X	LIN10	235 Product/Service ID Qualifier Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
X	LIN11	234 Product/Service ID	X 1 AN 1/48
X	LIN12	235 Product/Service ID Qualifier	X 1 ID 2/2

			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN13	234	Product/Service ID	X	1 AN 1/48
X	LIN14	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN15	234	Product/Service ID	X	1 AN 1/48
X	LIN16	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN17	234	Product/Service ID	X	1 AN 1/48
X	LIN18	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN19	234	Product/Service ID	X	1 AN 1/48
X	LIN20	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN21	234	Product/Service ID	X	1 AN 1/48
X	LIN22	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN23	234	Product/Service ID	X	1 AN 1/48
X	LIN24	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN25	234	Product/Service ID	X	1 AN 1/48
X	LIN26	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN27	234	Product/Service ID	X	1 AN 1/48
X	LIN28	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN29	234	Product/Service ID	X	1 AN 1/48
X	LIN30	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN31	234	Product/Service ID	X	1 AN 1/48

Segment: **SN1** Item Detail (Shipment)
Position: 0300
Loop: HL Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To specify line-item detail relative to shipment
Syntax Notes: 1 If either SN105 or SN106 is present, then the other is required.
Semantic Notes: 1 SN101 is the ship notice line-item identification.
Comments: 1 SN103 defines the unit of measurement for both SN102 and SN104.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	SN101	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	M 1 AN 1/20
M	SN102	382	Number of Units Shipped Numeric value of units shipped in manufacturer's shipping units for a line item or transaction set	M 1 R 1/10
M	SN103	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken EA= Each Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/2
	SN104	646	Quantity Shipped to Date Number of units shipped to date	O 1 R 1/15
	SN105	330	Quantity Ordered Quantity ordered	X 1 R 1/15
	SN106	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
	SN107	728	Returnable Container Load Make-Up Code Code identifying the load make-up of the returnable containers in the shipment Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 1/2
	SN108	668	Line Item Status Code Code specifying the action taken by the seller on a line item requested by the buyer Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 2/2

Segment: **REF** Reference Identification
Position: 1700
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>	
M	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification LS= Container ID: on the container label Refer to 004030 Data Element Dictionary for acceptable code values.	M	1 ID 2/3
M	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier UCC 128	M	1 AN 1/50
	REF03	352	Description A free-form description to clarify the related data elements and their content	X	1 AN 1/80
X	REF04	C040	Reference Identifier To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier	O	1
X	C04001	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	M	ID 2/3
X	C04002	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M	AN 1/50
X	C04003	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	X	ID 2/3
X	C04004	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN 1/50
X	C04005	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	X	ID 2/3
X	C04006	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN 1/50

Segment: **HL** Hierarchical Level
Position: 0100
Loop: HL Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Syntax Notes:
Semantic Notes:

- Comments:**
- 1 The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
The HL segment defines a top-down/left-right ordered structure.
 - 2 HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
 - 3 HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
 - 4 HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
 - 5 HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

Data Element Summary

Ref.	Data Element	Name	Attributes
M	HL01	Hierarchical ID Number A unique number assigned by the sender to identify a particular data segment in a hierarchical structure	M 1 AN 1/12
		4	
	HL02	Hierarchical Parent ID Number Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to	O 1 AN 1/12
		1	
M	HL03	Hierarchical Level Code Code defining the characteristic of a level in a hierarchical structure	M 1 ID 1/2
		S = Shipment I = Item O = Order P = Pack	
		Refer to 004030 Data Element Dictionary for acceptable code values.	
	HL04	Hierarchical Child Code Code indicating if there are hierarchical child data segments subordinate to the level being described	O 1 ID 1/1
		Refer to 004030 Data Element Dictionary for acceptable code values.	

Segment:	LIN Item Identification
Position:	0200
Loop:	HL Mandatory
Level:	Detail
Usage:	Mandatory
Max Use:	1
Purpose:	To specify basic item identification data
Syntax Notes:	<ol style="list-style-type: none"> 1 If either LIN04 or LIN05 is present, then the other is required. 2 If either LIN06 or LIN07 is present, then the other is required. 3 If either LIN08 or LIN09 is present, then the other is required. 4 If either LIN10 or LIN11 is present, then the other is required. 5 If either LIN12 or LIN13 is present, then the other is required. 6 If either LIN14 or LIN15 is present, then the other is required. 7 If either LIN16 or LIN17 is present, then the other is required. 8 If either LIN18 or LIN19 is present, then the other is required. 9 If either LIN20 or LIN21 is present, then the other is required. 10 If either LIN22 or LIN23 is present, then the other is required. 11 If either LIN24 or LIN25 is present, then the other is required. 12 If either LIN26 or LIN27 is present, then the other is required. 13 If either LIN28 or LIN29 is present, then the other is required. 14 If either LIN30 or LIN31 is present, then the other is required.
Semantic Notes:	1 LIN01 is the line item identification
Comments:	<ol style="list-style-type: none"> 1 See the Data Dictionary for a complete list of IDs. 2 LIN02 through LIN31 provide for fifteen different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

Data Element Summary

Ref.	Data	Element	Name	Attributes
M	LIN01	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	M 1 AN 1/20
M	LIN02	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) "VP" which stands for Vendor's (Seller) Part Number Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/2
M	LIN03	234	Product/Service ID Identifying number for a product or service Product Number	M 1 AN 1/48
M	LIN04	235	Product/Service ID Qualifier Code identifying the type/source of the descriptive number used in Product/Service ID (234) BP=Buyer's Part Number or PI= Purchaser's Item Number Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/2
M	LIN05	234	Product/Service ID Identifying number for a product or service Buyer's Part Number	M 1 AN 1/48
X	LIN06	235	Product/Service ID Qualifier Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
X	LIN07	234	Product/Service ID	X 1 AN 1/48
X	LIN08	235	Product/Service ID Qualifier Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
X	LIN09	234	Product/Service ID	X 1 AN 1/48
X	LIN10	235	Product/Service ID Qualifier Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
X	LIN11	234	Product/Service ID	X 1 AN 1/48
X	LIN12	235	Product/Service ID Qualifier	X 1 ID 2/2

			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN13	234	Product/Service ID	X	1 AN 1/48
X	LIN14	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN15	234	Product/Service ID	X	1 AN 1/48
X	LIN16	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN17	234	Product/Service ID	X	1 AN 1/48
X	LIN18	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN19	234	Product/Service ID	X	1 AN 1/48
X	LIN20	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN21	234	Product/Service ID	X	1 AN 1/48
X	LIN22	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN23	234	Product/Service ID	X	1 AN 1/48
X	LIN24	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN25	234	Product/Service ID	X	1 AN 1/48
X	LIN26	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN27	234	Product/Service ID	X	1 AN 1/48
X	LIN28	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN29	234	Product/Service ID	X	1 AN 1/48
X	LIN30	235	Product/Service ID Qualifier	X	1 ID 2/2
			Refer to 004030 Data Element Dictionary for acceptable code values.		
X	LIN31	234	Product/Service ID	X	1 AN 1/48

Segment: **SN1** Item Detail (Shipment)
Position: 0300
Loop: HL Mandatory
Level: Detail
Usage: Mandatory
Max Use: 1
Purpose: To specify line-item detail relative to shipment
Syntax Notes: 1 If either SN105 or SN106 is present, then the other is required.
Semantic Notes: 1 SN101 is the ship notice line-item identification.
Comments: 1 SN103 defines the unit of measurement for both SN102 and SN104.

Data Element Summary

	<u>Ref.</u> <u>Des.</u>	<u>Data</u> <u>Element</u>	<u>Name</u>	<u>Attributes</u>
M	SN101	350	Assigned Identification Alphanumeric characters assigned for differentiation within a transaction set	M 1 AN 1/20
M	SN102	382	Number of Units Shipped Numeric value of units shipped in manufacturer's shipping units for a line item or transaction set	M 1 R 1/10
M	SN103	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken EA= Each Refer to 004030 Data Element Dictionary for acceptable code values.	M 1 ID 2/2
	SN104	646	Quantity Shipped to Date Number of units shipped to date	O 1 R 1/15
	SN105	330	Quantity Ordered Quantity ordered	X 1 R 1/15
	SN106	355	Unit or Basis for Measurement Code Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken Refer to 004030 Data Element Dictionary for acceptable code values.	X 1 ID 2/2
	SN107	728	Returnable Container Load Make-Up Code Code identifying the load make-up of the returnable containers in the shipment Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 1/2
	SN108	668	Line Item Status Code Code specifying the action taken by the seller on a line item requested by the buyer Refer to 004030 Data Element Dictionary for acceptable code values.	O 1 ID 2/2

Segment: **REF** Reference Identification
Position: 1700
Loop: HL Mandatory
Level: Detail
Usage: Optional
Max Use: 1
Purpose: To specify identifying information
Syntax Notes:

- 1 At least one of REF02 or REF03 is required.
- 2 If either C04003 or C04004 is present, then the other is required.
- 3 If either C04005 or C04006 is present, then the other is required.

Semantic Notes:

- 1 REF04 contains data relating to the value cited in REF02.

Comments:

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>	
M	REF01	128	Reference Identification Qualifier Code qualifying the Reference Identification LS= Container ID: on the container label Refer to 004030 Data Element Dictionary for acceptable code values.	M	1 ID 2/3
M	REF02	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier UCC 128	M	1 AN 1/50
	REF03	352	Description A free-form description to clarify the related data elements and their content	X	1 AN 1/80
X	REF04	C040	Reference Identifier To identify one or more reference numbers or identification numbers as specified by the Reference Qualifier	O	1
X	C04001	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	M	ID 2/3
X	C04002	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	M	AN 1/50
X	C04003	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	X	ID 2/3
X	C04004	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN 1/50
X	C04005	128	Reference Identification Qualifier Code qualifying the Reference Identification Refer to 004030 Data Element Dictionary for acceptable code values.	X	ID 2/3
X	C04006	127	Reference Identification Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier	X	AN 1/50

Segment: **SE** Transaction Set Trailer
Position: 0200
Loop:
Level: Summary
Usage: Mandatory
Max Use: 1
Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Syntax Notes:

Semantic Notes:

Comments: 1 SE is the last segment of each transaction set.

Data Element Summary

	<u>Ref. Des.</u>	<u>Data Element</u>	<u>Name</u>	<u>Attributes</u>
M	SE01	96	Number of Included Segments Total number of segments included in a transaction set including ST and SE segments	M 1 N0 1/10
M	SE02	329	Transaction Set Control Number Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M 1 AN 4/9